

78L05T

Rev.J Mar.-2026



DATA SHEET

SOT-89

Voltage Regulator in a SOT-89 Plastic Package.

100mA,

3-Terminal regulators ,output current up to 100 mA, internal thermal overload protection and short-circuit limiting, HF Product.

Voltage Regulator.


/

*
*

Parameter	Symbol	Rating	Unit
Input voltage	V_I	30	V
Output current	I_O	100	mA
Operating Temperature Range	T_{OPR}	-40 125	
Power Dissipation	P_D	500	mW
Storage temperature range	T_{stg}	-55 150	


Thermal resistance junction-ambient R JA (-55)T.02.D.05536.46 607.04 .41a8 Tc[152 650.36

/ Electrical Characteristic Curve




SUT - 89

单位: 



/ Marking Instructions



H

L05

**

Note:

H: Company Code

L05: Product Type Code

** : Lot No. Code, code change with Lot No.

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- 1

150 180

60 90sec;

1.Preheating:150~180 , Time:60~90sec.
- 2

245±5

5±0.5sec;

2.Peak Temp.:245±5 , Duration:5±0.5sec.
- 3

2 10 /sec.

3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units					Dimension (unit mm ³)		
SOT-89	1,000	7	7,000	6	42,000	7 ×12	180×120×180	390×385×205

/ Notices