





	! " #	\$! % & '	! () % * +
--	-------	------------	-------------



a « « ¬ ® ¯ ° ± f 2 ¨

3 ´ % μ - ` ¶ . , 1 ° » ¼ % ½ £ , 1 ¨ ¾ , ¿ À Á 2KVC n o AEC-Q101 p q T r s t u v C Â Ã ï j ¨

L Ä Å Æ % Ç È ° É S μ - C w x g h f L % y A u v ¨



§

§

§

--	--



	(℃)		
	(℃)		
			℃
		~	℃
	θ .		℃
	$\theta \leq$		



ҚАЗАҚСТАН РЕСПУБЛИКАСЫНЫҢ БІЛІМ ЖӘНЕ ҒЫЛЫМ МИНИСТРЛІГІ

—		Ω				
—						







Figure 4 On-Resistance Variation with Temperature












Figure 9 : Safe Operation Area







Temperature Profile for IR Reflow Soldering(Pb-Free)



说明：

- 、预热温度 ~ °C，时间 ~ °C
- 、峰值温度 ± °C，时间持续为 ± °C
- 、焊接制程冷却速度为 ~ °C

温度： ± °C 时间： ± °C

卷盘包装

封装形式	包装数量					包装尺寸		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SOT-23	3,000	10	30,000	6	180,000	7" ×8	180×120×180	390×385×205