



SOT-323 NPN Silicon NPN transistor in a SOT-323 Plastic Package.

AEC-Q101
Low Cob, Qualified to AEC-Q101 Standards for High Reliability, HF Product.

General amplifier, Meet the stringent requirements of automotive applications.





PIN1 Base PIN 2 Emitter PIN 3 Collector

hFE Classifications Symbol	Q	R	S
hFE Range	120~270	180~390	270~560
Marking	QBQ	QBR	QBS

Rev.A Apr.-2023

Parameter





Q

B

Q h_{FE}


Note:

Q: Automobile halogen-free product Code

B: Product Type

Q: h_{FE} Classifications Symbol

Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- | | | | | | |
|---|-------|-----|-----------|---|--|
| 1 | 150 | 200 | 60 | 120sec; | 1.Preheating:150~200 , Time:60~120sec. |
| 2 | 255±5 | | 5±0.5sec; | 2.Peak Temp.:255±5 , Duration:5±0.5sec. | |
| 3 | | 2 | 10 /sec. | 3. Cooling Speed: 2~10 /sec. | |

260±5 10±1 sec. Temp:260±5 Time:10±1 sec

/ REEL

Package Type	Units					Dimension (unit mm ³)		
	Units/Reel	Reels/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Reel	Inner Box	Outer Box
SOT-323	3,000	10	30,000	6	180,000	7" ×8	180×120×180	390×385×205