

x


○

[illegible]

1 8

/ Electrical Characteristics(Ta=25)

/ Electrical Characteristic Curve



Ô ? d • Ž ¢ / Electrical Characteristic Curve


Ø □ =) ¢ / Package Dimensions

, M y f / Marking Instructions

^a ¢ y
(8 y , [W A
060N04 y ° Z W A

šWD t... •Žč (x/) / :KSVKXGZ[XK 6XULORK LUX /8 8KLRU] 9URJKXOTM 6

7HPSHUDWXUH



7LPH VHF

ačy

10•Ä½“† 150½180 - kž • 60½90sec;

20•Q>“† 245 r5 - kž • 4 Ò 5 r0.5sec;

30•D Nò i Ò 0 ,† 2½10 - /sec.

Note:

1.Preheating:150~180 - , Time:60~90sec.

2.Peak Temp.:245 r5 - , Duration:5 r0.5sec.

3. Cooling Speed: 2~10 - /sec.

ÂD /Cã p ¯ »] / Resistance to Soldering Heat Test Conditions

“†y 260 r5 -

ž •y 10 r1 sec.

Temp.:260±5

Time:10±1 sec

G P á / Packaging SPEC.

2 & x / REEL

Package Type / x ¥ "	Units ;>û H					Dimension ;>û p . (unit /mm³)		
	Units/Reel Q 2 &	Reels/Inner Box 2 & "	Units/Inner Box Q "	Inner Boxes/Outer Box " "	Units/Outer Box Q "	Reel	Inner Box	Outer Box
PDFN5×6	5,000	2	10,000	6	60,000	13"×12	360×360×50	380×335×366

„Đ y f / Notices