

/ Descriptions

SOT23-3 P MOS

P- CHANNEL MOSFET in a SOT23-3 Plastic Package.



/ Features

AEC-Q101

Trench FET@ Power MOSFET, Qualified to AEC-Q101 Standards for High Reliability, HF Product.

/ Applications

Primarily the display screen drive applications, Meet the stringent requirements of automotive applications.

/ Equivalent Circuit**/ Pinning**

PIN1 G

PIN 2 S

PIN 3 D

/ Marking

Marking	Q305
---------	------

BRCS2305MCQ

Rev.B Apr.-2023
B







DATA SHEET


/ Electrical Characteristics(Ta=25)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Turn-On Delay Time	$t_{d(on)}$	$V_{GS}=-4.5V$ $V_{DS}=-10V$ $R_L=2.22\Omega$ $R_{GEN}=3\Omega$		12		ns
Turn-On Rise Time	t_r			11.3		
Turn-Off Delay Time	$t_{d(off)}$			80		
Turn-Off Fall Time	t_f			32		

/ Electrical Characteristic Curve




/ Package Dimensions



IT23-3

SC

/ Marking Instructions



Q


305:

Note:

Q: Automobile halogen-free product Code

305 Product Type

() /



Note:

- | | | | | | |
|---|-------|-----|----|-----------|---|
| 1 | 150 | 200 | 60 | 120sec; | 1.Preheating:150~200 , Time:60~120sec. |
| 2 | 255±5 | | | 5±0.5sec; | 2.Peak Temp.:255±5 , Duration:5±0.5sec. |
| 3 | | 2 | 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SOT23-3	3,000	10	30,000	4	120,000	7" ×8	210×205×205	445×230×435

/ Notices