

/ Revised record

A	2019-7-18	ALL	SMA-S-SSL36-3A60V		
B	2021-6-7	4/7	b 5 50000 7 70000 340X340X40、350X350X230 336X336X40、380X335X366		



/ Descriptions

60V

3.0A

SMA

Surface Mount Schottky Barrier Rectifier, Reverse Voltage: 60V, Forward Current: 3.0A ,SMA thin package.

/ Features

Low power loss, high efficiency, High forward surge current capability, For use in low voltage, high frequency inverters, and polarity protection applications,For surface mounted applications.Halogen free product.

/ Applications

General purpose.


/ Equivalent Circuit



/ Pinning



The recommended mounting pad size



/ Marking

See Marking Instructions.

/ Absolute Maximum Ratings($T_a=25$)

参数 Parameter	符号 Symbol	数值 Rating	单位 Unit
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	60	V
Maximum RMS voltage	V_{RMS}	42	V
Maximum DC Blocking Voltage	V_{DC}	60	V
Maximum Average Forward Rectified Current at $T_c=100$ °C	$I_F(AV)$	3.0	A
Peak Forward Surge Current, 8.3ms Single Half Sine-wave Superimposed on Rated Load	I_{FSM}	80	A
Typical Junction Capacitance ¹⁾	C_i	400	pF
Typical Thermal Resistance ²⁾	$R_{\theta JA}$	60	°C/W
Operating Junction Temperature Range	T_j	-55~150	°C
Storage Temperature Range	T_{stg}	-55~150	°C


Note:

- 1) Measured at 1 MHz and applied reverse voltage of 4 V D.C
- 2) P.C.B. mounted with 2.0" X 2.0" (5 X 5 cm) copper pad areas.


/ Electrical Characteristics($T_a=25$)

参数 Parameter	符号 Symbol	测试条件 Test Conditions	数值 Rating	单位 Unit
Max Instantaneous Forward Voltage	V_F	$I_F=3.0A$	0.5	V
Maximum DC Reverse Current at Rated DC Reverse Voltage	I_R	$T_a=25$	0.3	mA
		$T_a=100$	5.0	

/ Electrical Characteristic Curve



/ Package Dimensions



/ Marking Instructions

Marking

Type	

/ Marking Instructions



SSL36

1

3


Note:

SSL36 Product Type Code

**** Lot No. Code The 1st means:YM Code The last 3 means:little Lot No
Code



() /



Note:

- | | | | | | |
|---|-------|-----|----|-----------|--|
| 1 | 150 | 180 | 60 | 90sec; | 1.Preheating:150~180°C, Time:60~90sec. |
| 2 | 245±5 | | | 5±0.5sec; | 2.Peak Temp.:245±5°C, Duration:5±0.5sec. |
| 3 | | | 2 | 10°C/sec. | 3. Cooling Speed: 2~10°C/sec. |

/ Resistance to Soldering Heat Test Conditions

260±5°C

10±1 sec.

Temp.:260±5°C

Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units					Dimension (unit mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box	Outer Box
SMA	5000	2	10000	7	70000	13" ×12	336X336X40	380X335X366

/ Notices