


Rev. A Qct.-2020

40V 5.0A SMB

Surface Mount Schottky Barrier Rectifiers, Reverse Voltage 40V, Forward Current: 5.0A, SMB package.

Low power loss, High efficiency, High forward surge current capability, For surface mounted applications. HF product.


General purpose.



PINNING

PIN	DESCRIPTION
1	Cathode
2	Anode

The recommended mounting pad size




Type number	Marking
SSL54B	SSL54

Parameter	Symbol	Rating	Unit
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	40	V
Maximum RMS voltage	V_{RMS}	28	V
Maximum DC Blocking Voltage	V_{DC}	40	V
Maximum Average Forward Rectified Current	$I_F (AV)$	5	A
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load	I_{FSM}	150	A
Typical Junction Capacitance ¹	C_j	800	pF
Typical Thermal Resistance ²	$R_{\theta JA}$	45	°C/W
Operating Junction Temperature Range	T_j	-55~+150	°C
Storage Temperature Range	T_{stg}	-55~+150	°C


Note:


- 1 Measured at 1 MHz and applied reverse voltage of 4 V D.C
- 2 P.C.B. mounted with 2.0" X 2.0" (5 X 5 cm) copper pad areas.

Parameter	Symbol	Test Conditions	数值 Rating	Unit
Maximum Instantaneous Forward Voltage	V_F	$I_F=5.0A$	0.45	V
Maximum DC Reverse Current at Rated DC Blocking Voltage	I_R	$T_a=25^{\circ}C$ $T_a=100^{\circ}C$	1 50	mA



SMB





SSL54

1 *

3 *


Note:

SSL54 Product Type Code

Lot No. Code The 1st * means:YM Code The last 3 * means:little Lot No
Code

Rev. A Qct.-2020

Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- | | | | |
|---|-----------|-------------|---|
| 1 | 150 ~ 180 | 60 ~ 90sec; | 1.Preheating:150~180 , Time:60~90sec. |
| 2 | 245±5 | 5±0.5sec; | 2.Peak Temp.:245±5 , Duration:5±0.5sec. |
| 3 | 2 ~ 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

260±5	10±1 sec.	Temp.:260±5	Time:10±1 sec
-------	-----------	-------------	---------------

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	只 卷盘	卷盘 盒	只 盒	盒 箱	只 箱		盒	箱
SMB	3000	5	15000	5	75000	7" ×11	185X180X105	390X385X205